

The LM2000 is a long range laser rangefinder for outdoor engineering. The main body is covered with anti-slip durable soft rubber that covers 80% of the entire device. LM2000 measure up to 2000 meters, equipped with 8X optical zoom. LM2000 is a highly accurate device designed for professionals. It is powered by 18650 lithium battery and charges through type-C USB cable.



| Specifications | Range |
|--------------------------|----------------------------|
| Certificates | CE, UKCA |
| Range | 2000m |
| Measuring unit | m/yd/ft |
| Accuracy | ±(0.3m+0.001×Dm) |
| Angle range | -90°~90° |
| Tilt angle accuracy | ±0.5° |
| Gyroscope angle accuracy | ±0.1° |
| Laser wavelength | 905nm |
| Field of view | 6° |
| Magnification | 8X |
| Object lens diameter | 23mm |
| Eyepiece diameter | 31mm |
| Exit pupil diameter | 3.8mm |
| Diopter | ±7D |
| Diopter adjustment | Manual |
| LCD display | Black (Red) bicolor R-Plcd |
| Charging interface | Type-C |
| Data export | USB |

| Features | |
|------------------------------------|---|
| Tripod screw hole | Flagpole lock mode (close-range priority) |
| Rain and fog (long-range priority) | Vertical height between two points |
| Point to point | Auto height/auto level |
| Auto power off | Continuous measurement |
| Angle measurement | Azimuth angle |

| Characteristics | |
|------------------------------|-------------------------|
| Power | 2000mAh Lithium battery |
| Product size | 149 x 125 x 55mm |
| Product net weight | 593g |
| Standard quantity per carton | 4pcs |
| Standard carton measurement | 400 x 335 x 120mm |
| Standard carton gross weight | 4.7kg |

