

## FEATURES

Universally usable analogue clamp meter in a compact housing 11 ranges in 4 functions

AC current measurement up to 300A

AC voltage measurement up to 600 V

DC voltage measurement up to 60 V

Resistance measurement up to 200k $\Omega$

Temperature measurement up to 150°C/300°F

Hold function

Clamp opening 40 mm

Power supply: 1 x 1.5V, IEC LR6/AA

Fuse 0.5A/250V

IEC 61010, CAT II/600V

## TECHNICAL SPECIFICATIONS

<b>DC Voltage</b>	60V
<b>Accuracy</b>	± (3% full scale)
<b>AC Voltage</b>	150/300/600V
<b>Accuracy</b>	± (3% full scale)
<b>AC Current</b>	6/15/60/150/300A
<b>Accuracy</b>	± (3% full scale)
<b>Resistance</b>	2K/200 K $\Omega$
<b>Accuracy</b>	± (4% full arc)
<b>Temperature</b>	-20v150°C/v300°F
<b>Accuracy</b>	± (5% full scale)
<b>Operating temperature</b>	0°C up to 40°C at RH< 80%
<b>Dimensions</b>	198 x 80 x 36mm
<b>Weight</b>	approx.320 g incl.battery



\*Technical Specifications & Appearance are subject to change without prior notice