



# Product data sheet

Power tools for trade & industry

Laser Measure

## GLM 120 C



The smart solution for measuring and documenting surroundings, even outdoors

### The most important data

Measurement range	0.08 – 120.00 m
Laser diode	650 nm, < 1 mW
Weight, approx.	0.21 kg

**Part Number** 0 601 072 F70

[> More product information](#)

## Technical data

### Technical data

Laser diode	650 nm, < 1 mW
Measurement range	0.08 – 120.00 m
Laser class	2
Measurement accuracy, typical	± 1.5 mm* (*plus use-dependent deviation)
Measurement range of incline measurement	0 – 360° (4 x 90°)
Measuring accuracy (typical)	± 0.2°* (*plus use-dependent deviation)
Measurement time, typical	< 0.5 s
Measurement time, max.	4 s
Power supply	1 x 3.6 V Li-Ion battery (3120 mAh)
Automatic deactivation	5 min
Weight, approx.	0.21 kg
Units of measurement	m/cm/mm/ft/inch/ ft-inch
Memory capacity (values)	50
Dust and splash protection	IP 54
Tripod thread	1/4"
Digital viewfinder	integrated
Data transfer	Bluetooth™ 4.2 Low Energy

Laser colour	Red
--------------	-----



# Product data sheet

Power tools for trade & industry

---

## Advantages:

- Digital viewfinder with zoom function allows for precision over large distances, outdoors and in complex surroundings
- High-contrast IPS colour display provides optimal readability
- Remote controlling for rapid measurements and MeasureOn App for simple results documentation

