



Cable and underground infrastructure locator

LKZ-1500 / LKZ-1500-LITE

index: WMGBLKZ1500 / WMGBLKZ1500LITE

LKO-1500 / LKO-1500-LITE

index: WMGBLKO1500 / WMGBLKO1500LITE

LKN-1500

index: WMGBLKN1500



LKO-1500
receiver

LKN-1500
transmitter

LKO-1500-LITE
receiver



LKZ-1500

LKZ-1500-LITE

Underground detectives

Features

The LKZ locator set consists of a LKN transmitter and LKO receiver. It allows for location, identification and tracking of the route of objects buried in the earth. The user will be able to trace:

- power cords and cables, control cables, telecommunications cables,
- underground elements of lightning protection systems, cathodic protection systems,
- water and sewage systems,
- fuel transmission systems (pipelines, gas pipelines)
- heating systems and pre-insulated pipes.

The sets of LKZ series are an invaluable support in earthworks carried out for various industries, including energy, installation, construction, railway, telecommunications, water and sanitary, heating, geodetic and many others.

LKN-1500 transmitter introduces a specific signal to the tracked objects, enabling LKO receivers to route in the active mode. The receivers operate also in a passive mode that uses the network frequencies and telecommunications signals present in the facility.

LKO-1500-LITE receiver is designed according to "intuitive and user-friendly" principle and it is an ideal solution for users entering the world of cable location and routing. **LKO-1500 receiver** is a level higher: it facilitates the work of the user to with many features, including visualization of the cable routing in the tested object or a greater number of frequencies to choose from. It is also distinguished by the option of tracing cable short-to-earth faults with the use of additional accessories.



LKN-1500 transmitter

- Transmission of double frequency signals.
- The mode of limiting the voltage of the transmitted signal.
- Transmitter power: 1 W, 2 W, 5 W, 10 W.
- Operation in direct galvanic or inductive connection mode - internal transmitting antenna.
- Compatible with transmitting clamps.
- Continuous or interval mode of operation that extends battery life.
- Case housing.


LKO-1500-LITE receiver


- **Active mode**
 - » work with LKN-1500 transmitter at the frequencies of 1024 Hz, 8928 Hz, 33 kHz.
- **Passive mode** – work at the frequencies of:
 - » 50 Hz,
 - » RADIO (10...36 kHz),
 - » SB (48 Hz...14 kHz).
- Location depth up to 6 m.



LKO-1500 receiver

- **Active mode:**
 - » work with LKN-1500 transmitter at the frequencies of 273 Hz, 526 Hz, 1024 Hz, 8928 Hz, 33 kHz,
 - » work with transmitters other than LKN-1500 at the frequencies of 491 Hz, 512 Hz, 982 Hz, 2000 Hz, 2048 Hz, 8440 Hz, 9828 Hz, 10000 Hz.
- **Passive mode** – work at the frequencies of:
 - » 50 Hz, 60 Hz, 100 Hz, 300 Hz, 550 Hz, 1450 Hz,
 - » RADIO (10...36 kHz),
 - » SB (48 Hz...14 kHz).
- Location depth up to 10 m.
- Operation with external probes.






Sonel LKZ Terminal

The application works with the Sonel LKZ-1500 wire and cable locator. By replacing the external GPS module, it allowing the user to define and record the geographic coordinates of the cable route.

The application additionally enables:


- live positioning preview,
- measuring the distance to a specific point on the route,
- export of routes saved in LKO-1500 to the phone's memory,
- reading routes from the phone's memory,
- preview of the saved values of all parameters,
- data export to PC.



Sonel LKO Terminal

A dedicated PC program for handling data stored in Sonel LKO-1500. It allows you to map a route from your location and read the data stored in the receiver. The data includes:

- coordinates of the place of measurement according to GPS information,
- reading the depth of the object and value of current flowing in it,
- the direction of the forced current,
- operating frequency,
- date and local time at the time of measurement according to GPS information,
- export of route data to a file.



Technical specifications

LKN-1500 transmitter

Ingress protection	IP54
Power supply	VRLA (AMG) lead-acid 12 V / 7 Ah
Dimensions	275 x 250 x 180 mm
Weight	ca. 4.9 kg
Operating temperature	-20...+55°C
Storage temperature	-50...+70°C
Nominal temperature	23 ± 2°C
Relative humidity	no more than 90% at the temperature of +30°C

LKO-1500 / 1500-LITE receiver

Ingress protection	IP54
Power supply	Ni-MH 6 V/2000 mAh battery pack 5x AA 1.5 V battery 5x Ni-MH 1.2 V rechargeable battery
Dimensions	700 x 300 x 140 mm
Weight	
LKO-1500-LITE	ca. 1.7 kg
LKO-1500	ca. 1.8 kg
Operating temperature	-20...+55°C
Storage temperature	-50...+70°C
Nominal temperature	23 ± 2°C
Relative humidity	no more than 95% at the temperature of +30°C



LKZ-1500 • LKZ-1500-LITE | Standard accessories



**LKN-1500
transmitter**



**LKO-1500
receiver**
only for LKZ-1500



**LKO-1500-LITE
receiver**
only for LKZ-1500-LITE



**Crocodile clip 1 kV
20 A red / blue**

WAKRORE20K02
WAKROBU20K02



Sun-protecting cover
only for LKZ-1500

WAPOZOSL4



**Test lead 5 m 1 kV
(banana plugs)
red / blue**

WAPRZ005REBB
WAPRZ005BUBB



Hanging strap
only for LKZ-1500

WAPOZSZE6




Ground probe 23 cm

WASONG23



Bag L13

WAFUTL13



Power supply

Battery compartment
WAPOJ3

Rechargeable battery
NiMH 6 V, 2 Ah
WAAKU23

Battery charger Z16
WAZASZ16

Battery charger Z17
WAZASZ17

LKO-1500 • LKO-1500-LITE | Optional accessories



Hanging strap
only for LKO-1500

WAPOZSZE6



Sun-protecting cover
only for LKO-1500

WAPOZOSL4



Bag L13

WAFUTL13



Power supply

Battery compartment
WAPOJ3

Rechargeable battery
NiMH 6 V, 2 Ah
WAAKU23

Battery charger Z17
WAZASZ17

LKN-1500 | Standard accessories



**Crocodile clip 1 kV
20 A red / blue**

WAKRORE20K02
WAKROBU20K02



**Test lead 5 m 1 kV
(banana plugs)
red / blue**

WAPRZ005REBB
WAPRZ005BUBB



Battery charger Z16

WAZASZ16



Ground probe 23 cm

WASONG23

LKZ-1500 / 1500-LITE • LKO-1500 • LKN-1500 | Optional accessories



Transmitting clamps
only for
• LKZ-1500 / 1500-LITE
• LKN-1500

N-1 (fi 52 mm)
WACEGN1BB

N-4 (fi 110 mm)
WACEGN4

N-5 (fi 125 mm)
WACEGN5



GPS adapter GT-750
only for
• LKZ-1500
• LKO-1500

WAADAGT750



Probes

only for
• LKZ-1500
• LKO-1500

DKI probe
WASONDKI

A-frame
WAADALKZRA2