

UT306A is a portable non-contact thermometer. This device's miniature design is convenient to carry and suitable for everyday temperature measurement needs. UT306A is designed to counter environmental interference, ensuring accurate temperature readings under various measurement environments.



UT306A

Specifications	UT306A
Certificates	CE, UKCA
Temperature range (°C)	-35°C~300°C
Temperature range (°F)	-31°F~572°F
Accuracy (°C)	±2°C or ±2%
Accuracy (°F)	±4°F or ±2%
D:S ratio	6:1
Response time	<250ms
Emissivity	0.95
Spectral response	8μm~14μm
Laser power	<1mW
Operating temperature	0°C~50°C (32°F~104°F)
Storage temperature	-20°C~60°C (-4°F~140°F)
Operating humidity	<90%RH (non-condensing)
Drop proof	1m

Features	
Auto power off	MAX/MIN/AVG mode
Low battery indication	Lock measurement
Data hold	Backlight
°C/°F selection	Laser on/off

Characteristics	
Standard accessories	Batteries, English manual
Power	1.5V battery (R03) x 3
Display	37.4 x 36.4mm
Product size	120 x 53 x 28mm
Product net weight	120g
Standard individual packing	Gift box
Standard quantity per carton	20pcs
Standard carton measurement	272 x 225 x 200mm
Standard carton gross weight	2.8kg