



# **Smart & Wireless**

## **Thermo-hygrometer\***

#### testo 605i

Quickly and accurately measures relative humidity and temperature in rooms, ducts, and chambers

Automatically calculates dew point & wet bulb temperature

Small diameter probe is ideal for in-duct measurements

Measurement data is transmitted to the convenient and powerful testo **Smart Probes App** in your smart device

Tough, accurate, and easy-to-use

For all HVAC/R technicians and contractors



\*Operates with iOS or Android smart devices such as smart phones, tablets, etc.

The testo 605i Smart Probe thermo-hygrometer is a humidity and temperature measuring instrument that quickly and accurately measures relative humidity, dew point, and temperature in rooms, ducts, registers, and environmental boxes/chambers. Users can read the measurements using the testo *Smart Probes App* installed on their smart device. Smart Probes can be used individually or combined with other Smart Probes to create measuring solutions for most HVAC/R applications. Great for setup and diagnostics of large and small HVAC/R systems!

The testo 605i works on smart devices with either Android or Apple operating systems.

The testo **Smart Probes App** is a powerful and easy-touse tool. It allows you to remotely read measurements from up to six (6) Smart Probes and easily document/report the results. Automatic calculations make it a snap! All measurement data is displayed as instrument readings, tables, or graphs. The measurements can be quickly saved as PDF or Excel files. The App creates custom reports which can be saved and/or shared by email. All your data can be stored and retrieved <u>saving you hours</u> of time consuming paperwork!

## info@Testo-Direct.com

www.**Testo-Direct**.com

## 1.888.610.7664

## **Technical data/accessories**

#### testo 605i

testo 605i, Bluetooth thermo-hygrometer with App, incl. 3 AAA batteries and certificate of calibration

Order no. 0560 1605



Sensor type	Humidity – capacitive
Measuring range	0 to 100% RH
Accuracy	±(1.8% RH + 3% of m.v.) at 77 °F (5 to 80% RH)
Resolution	0.1% RH
Sensor type	NTC
Sensor type Measuring range	<b>NTC</b> -4 to 140 °F

# 72.1. 48.7

#### **Testo Smart Probes App**

The Testo Smart Probes App combines the power of your smart phone/tablet with the accurate measurements of your Smart Probes. The operation and display of the instruments are communicated via Bluetooth to the App on your smart phone or tablet . The Smart Probes App uses the measurements to create custom reports (including added photos and comments). Information and reports can be saved as files and/or sent by e-mail. For Apple iOS and Android.





VAC Smart Probe Kit: 0563 0003

General technical data		
Compatibility	requires iOS 8.3 (or later) / Android 4.3 (or later)	
	requires mobile device with Bluetooth 4.0	
Storage temperature	-4 to 140 °F	
Operating temperature	-4 to 122 °F	
Battery type	3 AAA Batteries (incl.)	
Battery life	250 hrs	
Dimensions	9.6 x 1.2 x 0.9 in	
	Probe shaft: 3.4 in (L), 0.5 (dia.)	
Warranty	2 years	
Measuring Units	°F, °C, %rF / %RH, °Ftd, °Ctd, wetbulb °F wetbulb °C	

#### Order no.

Accessories	Order no.
testo VAC Smart Probe Kit for servicing ventilation and air conditioning systems. Includes: testo 405i, testo 410i, testo 605i, testo 805i. Dimensions 10.6 x 7.5 x 2.4 in	0563 0003
testo Smart Case (VAC) for the storage and transport of testo 405i, testo 410i, testo 510i, testo 605i, testo 805i and testo 905i Dimensions 10.6 x 7.5 x 2.4 in	0516 0260

info@Testo-Direct.com

www.**Testo-Direct**.com

1.888.610.7664