

BESANTEK Large Display Thermo-Hygrometer widely applied to laboratory fields, food industry, medical application, pharmaceutical industry, industrial application, environmental protection areas and agricultural research fields.

Features:

- Adaptive and highly sensitive sensor with fast response and high accuracy.
- Indoor and outdoor temperature measuring.
- Indoor humidity measuring.
- Selectable °C or °F.
- Large LCD display.
- Max./Min. and current value displayed.
- Clock date is displayed.
- Reliable and stable.
- Accessories: Instruction manual, external temperature probe and battery.

Technical Specification:

BST-HYG2	
Indoor Temperature Range	-10 to 50°C (14 to122°F)
Outdoor Temperature Range	-50 to 70°C (-58 to 158°F)
Temperature Resolution	0.1°C (0.2°F)
Temperature Accuracy	±1°C (±1.8°F)
Humidity Range	10%RH to 90%RH
Humidity Resolution	1%RH
Humidity Accuracy	±5.0%RH
Sensor Cable Length	2m
Power Source	1.5V (AAA) x 1
Dimensions	103 x 96 x 20 mm
Weight	Approx. 115g

Ordering Information:

• BST-HYG2: Large Display Thermo-Hygrometer.



BST-HYG2



Safety Standard: • EN 61326-1: 2013, EN 61326-2-2: 2013

> www.besantek.ca info@besantek.ca

BESANTEK Corporation, CANADA