

## Hioki 3030-10 Analog HiTester Multimeter



勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

### Basic tester with improved safety features

- Protected against transient voltages up to 250 V AC, preventing electric shock accidents before they can happen
- Drop proof design withstands dropping onto a concrete floor from a height of 1 meter
- LED check function
- Temperature measurement support (with optional probes)
- CE marking

Specifications	
<b>DC Voltage range</b>	0.3 V (16.7 k-ohm/V), 3/12/30/120/300/600 V (20 k-ohm/V) Accuracy: $\pm 2.5$ % f.s.
<b>AC Voltage range</b>	12 V (9 k-ohm/V) Accuracy: $\pm 4$ % f.s. 30/120/300/600 V (9 k-ohm/V) Accuracy: $\pm 2.5$ % f.s. Average rectifier effective value
<b>Resistance range</b>	0 to 3 k-ohm ( center scale 30 ohm), R $\times$ 1, R $\times$ 10, R $\times$ 100, R $\times$ 1 k Accuracy: $\pm 3$ % of scale length
<b>DC Current range</b>	60 $\mu$ A/30 m/300 mA (300 mV internal voltage drop) Accuracy: $\pm 3$ % f.s.
<b>Other functions</b>	Battery check: 0.9 to 1.8 V, load resistance 10 ohm Temperature: -20 to 150 $^{\circ}$ C ( 9021-01 Thermister Temperature Probe is necessary, sold separately)
<b>Safety considerations</b>	Complies with EN61010-1:1992+A2:1995, EN61010-2-031:1994, Installation Category III (anticipated transient overvoltage 6000 V), Pollution Degree 2
<b>Power supply</b>	R6P(AA) $\times$ 2 batteries
<b>Dimensions, mass</b>	95 mm(3.74 in)W $\times$ 141 mm(5.55 in)H $\times$ 39 mm(1.54 in)D, 280 g (9.9 oz)