

**TECHNICAL DATA** 

# Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers



## **Key features**

- 6-digit backlight display reads the data clearly
- Signal detection reminder avoids invalid detection actions
- Maximum/minimum/average value and final readings
- Setting/Turning off the automatic power-off function
- Small size and easy to hold
- Easy switching of the contact and non-contact measurement modes
- Different speed measuring heads and rotational speeds adapt to different measurement occasions
- 1-year warranty

### Product overview: Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers

The Fluke 931 tachometer is a handheld tachometer, which integrates the contact and non-contact speed measurement functions and can accurately measure the revolutions per minute (RPM) or surface speed and distance. Fluke 930 is equivalent to a Fluke 931 with minimum configuration. With only the non-contact measuring function provided, it's more affordable and offers consistent quality.

#### **Applications:**

- Heavy manufacturing environments, e.g. automotive, textile, pulp and paper, metalwork
- Water purification plants



- Machining and chemical manufacturing plants
- HVAC compressors for industrial systems

## Specifications: Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers

#### **Rotation speed measurement**

| •                |   |
|------------------|---|
| Range            | Optical (non-contact) measurement: 1 to 99999 revolutions/minute<br>Contact measurement: 1 to 19999 revolutions/minute (Fluke 931 only) |
| Precision        | ±0.02%RD+1  |
| Sensing distance | (optical) 500 mm  |

| Specifications        |                                    |  |
|-----------------------|------------------------------------|--|
| Battery type          | (2) 1.5V LR6 (alkaline) AA battery |  |
| Battery life          | About 40 hours                     |  |
| Operating temperature | 0°C to 50°C                        |  |
| Storage temperature   | -20°C to 70°C                      |  |
| Weight                | 250 g                              |  |
| Dimensions            | 175 × 60 × 28 mm                   |  |
| Warranty period       | 1 year                             |  |



### **Ordering information**



### Fluke 931

Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers

- 0.1 m wheel
- Conical speed measuring head
- Inner cone speed measuring head
- Lengthening rod
- 10 reflective stripes



#### Fluke. Keeping your world up and running.®

Fluke Corporation PO Box 9090, Everett, WA 98206 U.S.A.

#### For more information call:

In the U.S.A. (800) 443-5853 In Canada (800) 36-FLUKE From other countries +1 (425) 446-5500 www.fluke.com ©2023 Fluke Corporation. Specifications subject to change without notice. 06/2023

Modification of this document is not permitted without written permission from Fluke Corporation.